

THERMACUT[®]
THE CUTTING COMPANY[™]

PLASMA CUTTING SYSTEM

EX-TRAFIRE[®] 125HD



CUTTING MAX.
2 1/2"

DUTY CYCLE
100 % @ 125 A

INCL.
MARKING

WWW.EX-TRAFIRE.COM

INDUSTRIAL CUTTING. HEAVY-DUTY PERFORMANCE.

The plasma cutting systems in the **EX-TRAFIRE®HD** range are the absolute specialists in meeting tough demands in continuous operation. The mobile **EX-TRAFIRE®125HD** plasma cutting system with 100 % duty cycle is the perfect solution for demanding heavy duty applications in industry.



Heavy
Fabrication



Structural



Shipyards
and Offshore



Steel Mills and
Steel Service Center



General
Fabrication






EX-TRAFIRE® 125HD PLASMA CUTTING SYSTEM.

IMPRESSIVE PERFORMANCE



- + Extremely high cutting speed
- + Maximum cutting quality, even with long cuts
- + Also ideal for automated processes

HIGHEST FLEXIBILITY



- + Plate thicknesses up to 2½ "
- + For mechanized and manual applications
- + Gouging with high removal rate
- + Suitable for worldwide use

SIMPLE OPERATION



- + Large 4" LCD color display
- + Clear control panel
- + Self-explanatory icons
- + TCS for quick torch replacement

OPTIMAL COST-EFFECTIVENESS



- + Low investment costs
- + 20 % longer consumable lifetime
- + Low operating costs
- + 100% duty cycle for maximum productivity

NEW CUTTING TORCH FHT®EX125TT



- + Torch design award winner
- + Optimized ergonomics
- + Relaxed PE and PA cutting
- + 100% duty cycle

MARKING



- + Automatic gas identification (air, nitrogen, argon)
- + Integrated gas-saving function
- + Fine, deep or wide markings
- + Optional Smooth-Marking for applications below 20 A marking current

READY FOR INDUSTRY 4.0



- + Industry leading connectivity
- + CAN / RS 485 and RS 422 interfaces (optional)
- + Easy monitoring
- + Expandable and updatable


AUTOMATIC SETTINGS



- + Cutting gas type, electricity and pilot current
- + Compensation for pressure drops
- + Fewer operating errors, better cutting quality

EX-TRAFIRE® 125HD

PLASMA CUTTING SYSTEM.



SPECIFICATION

Severance [in]	2½ ⁽¹⁾
Recommended [in]	1½ ⁽¹⁾
Piercing [in]	1 ⁽¹⁾
Gouging removal [lbs/hr]	17.6

DUTY CYCLE (104 °F/ 145 V)

100 %	@ 125 A
-------	---------

OUTPUT (VDC)

Nominal [V]	180
-------------	-----

INPUT

Voltage (VAC) [V/Hz]	3×480 VAC or 3×575±15 % ⁽²⁾ 50/60
Compressed air flow [lpm@psi]	200/72.5
Recommended min/max pressure [psi]	95-145

MACHINE DATA

Dimensions L x W x H [in]	24" x 20" x 12"
Weight [lbs]	75

TORCH (HAND/MACHINE)

FHT EX® 125TT

Designed to interface with a variety of CNC machines

(1) related to low-alloy steel (mild steel)

(2) suitable for generator use

THINK FRESH. CUT ORANGE.

THERMACUT® comes up with fresh ideas for cutting technology. Benefit from innovative, reliable, powerful and highly efficient cutting solutions.



Discover the other plasma cutting systems within the **EX-TRAFIRE® HD** family and our wide range of cutting solutions at www.thermacut.com

WWW.THERMACUT.COM
SALES@THERMACUT.COM

follow
#EXTRAFIRE



THERMACUT®, THE CUTTING COMPANY®, FHT-EX®, EX-TRAFIRE®, EX-TRACK®, EX-TRABEAM® AND EX-TRAFIAME® ARE REGISTERED TRADEMARKS OF THERMACUT, K.S. AND MAY BE REGISTERED IN CZECH REPUBLIC AND/OR OTHER COUNTRIES. ALL OTHER TRADEMARKS ARE PROPERTIES OF THEIR RESPECTIVE OWNERS.